



IN THE CLAIMS:

Please amend the claims as indicated below.

1. (Previously Presented) A method for restricting access of a user to a  
5 restricted item, said method comprising the steps of:  
    providing a token to said user using a first communication channel;  
    instructing said user to enter said provided token using a cellular telephone  
    that has been previously associated with said user; and  
    providing access to said user if said entered token matches said provided  
10 token and is received via a wireless connection from a cellular telephone having a serial  
    number previously associated with said user.
2. (Original) The method of claim 1, further comprising the step of receiving  
a password from said user before providing said token.
- 15 3. (Original) The method of claim 1, wherein said token is a pseudo-random  
number.
4. (Original) The method of claim 1, wherein said instructing step further  
20 comprises the step of instructing said user to dial an access control administrator to enter  
said token.
5. (Original) The method of claim 4, further comprising the step of providing  
said token to said access control administrator.
- 25 6. (Original) The method of claim 4, further comprising the step of providing  
a telephone number associated with said associated cellular telephone to said access  
control administrator.
- 30 7. (Original) The method of claim 4, further comprising the step of providing  
an amount for approval to said access control administrator.

8. (Original) The method of claim 4, wherein said access control administrator compares said token received from said user to said provided token.

9. (Original) The method of claim 4, wherein said access control administrator ensures that said token is received from a cellular telephone having a serial number previously associated with said user.

10. (Original) The method of claim 1, wherein said instructing step further comprises the step of establishing a connection over a cellular network to said cellular telephone associated with said user and instructing said user to enter said token.

11. (Previously Presented) A method for restricting access of a user to a restricted item, said method comprising the steps of:

providing a token to an access control administrator;

providing said token to said user using a first communication channel;

instructing said user to dial a telephone number associated with said access control administrator using a cellular telephone that has been previously associated with said user to enter said provided token; and

providing access to said user if said entered token matches said provided token and is received via a wireless connection from a cellular telephone having a serial number previously associated with said user.

12. (Original) The method of claim 11, wherein said access control administrator compares said entered token to said provided token.

13. (Original) The method of claim 11, further comprising the step of providing a cellular telephone number that has been previously associated with said user to said access control administrator and wherein said access control administrator determines a cellular telephone number associated with a serial number of a cellular telephone from which said token was received and compares said provided cellular telephone number with said determined cellular telephone number.

14. (Original) The method of claim 11, further comprising the step of receiving an indication from said access control administrator indicating that said entered token matches said provided token and was received from a cellular telephone having a serial number previously associated with said user.

5

15. (Original) The method of claim 11, further comprising the step of receiving a password from said user before providing said token.

16. (Original) The method of claim 11, wherein said token is a pseudo-random number.

10

17. (Previously Presented) A method for restricting access of a user to a restricted item, said method comprising the steps of:

providing a token to said user using a first communication channel;

15

establishing a connection over a cellular network to a cellular telephone associated with said user;

instructing said user to enter said provided token using said cellular connection; and

20

providing access to said user if said entered token matches said provided token and is received via a wireless connection from a cellular telephone having a serial number previously associated with said user.

18. (Original) The method of claim 17, further comprising the step of receiving a password from said user before providing said token.

25

19. (Original) The method of claim 17, wherein said token is a pseudo-random number.

20. (Previously Presented) A system for restricting access of a user to a restricted item, comprising:

30

a memory that stores computer-readable code; and

a processor operatively coupled to said memory, said processor configured to implement said computer-readable code, said computer-readable code configured to:  
provide a token to said user using a first communication channel;  
instruct said user to enter said provided token using a cellular telephone  
5 that has been previously associated with said user; and  
provide access to said user if said entered token matches said provided token and is received via a wireless connection from a cellular telephone having a serial number previously associated with said user.

10 21. (Previously Presented) A system for restricting access of a user to a restricted item, comprising:

a memory that stores computer-readable code; and  
a processor operatively coupled to said memory, said processor configured to implement said computer-readable code, said computer-readable code configured to:  
15 provide a token to an access control administrator;  
provide said token to said user using a first communication channel;  
instruct said user to dial a telephone number associated with said access control administrator using a cellular telephone that has been previously associated with said user to enter said provided token; and  
20 provide access to said user if said entered token matches said provided token and is received via a wireless connection from a cellular telephone having a serial number previously associated with said user.

22. (Previously Presented) A system for restricting access of a user to a  
25 restricted item, comprising:

a memory that stores computer-readable code; and  
a processor operatively coupled to said memory, said processor configured to implement said computer-readable code, said computer-readable code configured to:  
provide a token to said user using a first communication channel;  
30 establish a connection over a cellular network to a cellular telephone associated with said user;

instruct said user to enter said provided token using said cellular connection; and

provide access to said user if said entered token matches said provided token and is received via a wireless connection from a cellular telephone having a serial  
5 number previously associated with said user.

23. (Previously Presented) A system for restricting access of a user to a restricted item, comprising:

means for providing a token to said user using a first communication  
10 channel;

means for instructing said user to enter said provided token using a cellular telephone that has been previously associated with said user; and

means for providing access to said user if said entered token matches said provided token and is received via a wireless connection from a cellular telephone having  
15 a serial number previously associated with said user.

24. (Previously Presented) An article of manufacture for restricting access of a user to a restricted item, comprising:

a computer readable medium having computer readable code means  
20 embodied thereon, said computer readable program code means comprising:

a step to provide a token to said user using a first communication channel;

a step to instruct said user to enter said provided token using a cellular telephone that has been previously associated with said user; and

a step to provide access to said user if said entered token matches said  
25 provided token and is received via a wireless connection from a cellular telephone having a serial number previously associated with said user.

25. (Previously Presented) An article of manufacture for restricting access of a user to a restricted item, comprising:

30 a computer readable medium having computer readable code means embodied thereon, said computer readable program code means comprising:

a step to provide a token to an access control administrator;  
a step to provide said token to said user using a first communication channel;

a step to instruct said user to dial a telephone number associated with said  
5 access control administrator using a cellular telephone that has been previously  
associated with said user to enter said provided token; and

a step to provide access to said user if said entered token matches said  
provided token and is received via a wireless connection from a cellular telephone having  
a serial number previously associated with said user.

10  
26. (Previously Presented) An article of manufacture for restricting access of a  
user to a restricted item, comprising:

a computer readable medium having computer readable code means  
embodied thereon, said computer readable program code means comprising:

15 a step to provide a token to said user using a first communication channel;  
a step to establish a connection over a cellular network to a cellular  
telephone associated with said user;

a step to instruct said user to enter said provided token using said cellular  
connection; and

20 a step to provide access to said user if said entered token matches said  
provided token and is received via a wireless connection from a cellular telephone having  
a serial number previously associated with said user.

27. (New) A method for restricting access of a user to a restricted item, said  
25 method comprising the steps of:

providing a token to said user using a first communication channel;  
receiving said provided token from said user via a cellular telephone that  
has been previously associated with said user; and

providing access to said user if said entered token matches said provided  
30 token and is received via a wireless connection from a cellular telephone having a serial  
number previously associated with said user.

28. (New) The method of claim 27, further comprising the step of receiving a password from said user before providing said token.

29. (New) The method of claim 27, wherein said token is a pseudo-random  
5 number.

30. (New) The method of claim 27, wherein said receiving step further comprises the step of instructing said user to dial an access control administrator to enter said token.  
10

31. (New) The method of claim 27, further comprising the step of establishing a connection over a cellular network to said cellular telephone associated with said user and instructing said user to enter said token.